

A Bulb-IC Driver

A泡-驱动分离



3200K/6500K



Wattage 瓦数	Diameter Size 灯体尺寸	Led chip 灯珠	PF 功率因素	Total LM 总流明
5W	Φ50mm*90mm	1*6V-2835-6D	≥0.5	450LM
7W	Φ55mm*102mm	1*6V-2835-8D	≥0.5	630LM
9W	Φ60mm*112mm	1*6V-2835-10D	≥0.5	790LM
12W	Φ65mm*118mm	1*6V-2835-13D	≥0.5	1002LM
15W	Φ70mm*135mm	1*6V-2835-16D	≥0.5	1237LM
18W	Φ80mm*150mm	1*6V-2835-20D	≥0.5	1504LM

A Bulb-IC DOB

A泡



3200K/6500K



CE CB



Wattage 瓦数	Diameter Size 灯体尺寸	Led chip 灯珠	PF 功率因素	Total LM 总流明
5W	Φ50mm*90mm	2835-6D	≥0.5	423LM
7W	Φ55mm*102mm	2835-8D	≥0.5	601LM
9W	Φ60mm*113mm	2835-10D	≥0.5	766LM
12W	Φ65mm*120mm	2835-13D	≥0.5	1039LM
15W	Φ70mm*135mm	2835-16D	≥0.5	1273LM
18W	Φ80mm*150mm	2835-18D	≥0.5	1508LM

T Bulb-IC Driver

白云款-驱动分离



3200K/6500K



Wattage 瓦数	Diameter Size 灯体尺寸	Led chip 灯珠	PF 功率因素	Total LM 总流明
5W	Φ50mm	2835-6D	≥0.5	524LM
9W	Φ60mm	2835-11D	≥0.5	895LM
13W	Φ70mm	2835-15D	≥0.5	1402LM
18W	Φ80mm	2835-21D	≥0.5	1725LM
28W	Φ100mm	2835-32D	≥0.5	2641LM
38W	Φ115mm	2835-42D	≥0.5	3721LM
48W	Φ125mm	2835-50D	≥0.5	4417LM
58W	Φ140mm	2835-60D	≥0.5	5127LM

T Bulb-DOB

白云款



3200K/6500K



Wattage 瓦数	Diameter Size 灯体尺寸	Led chip 灯珠	PF 功率因素	Total LM 总流明
5W	Φ50mm	2835-6D	≥0.5	550LM
9W	Φ60mm	2835-11D	≥0.5	924LM
13W	Φ70mm	2835-16D	≥0.5	1408LM
18W	Φ80mm	2835-22D	≥0.5	1920LM
28W	Φ100mm	2835-36D	≥0.5	2923LM
38W	Φ115mm	2835-45D	≥0.5	3671LM
48W	Φ125mm	2835-54D	≥0.5	4543LM
58W	Φ135mm	2835-65D	≥0.5	5356LM

New T Bulb-IC DOB

新款条纹T泡 塑包铝



3200K/6500K



Wattage 瓦数	Diameter Size 灯体尺寸	Led chip 灯珠	PF 功率因素	Total LM 总流明
5W	Φ50mm	2835-6V-1W-5D	≥0.5	400.75LM
9W	Φ60mm	5730-12V-2W-5D	≥0.5	775.92LM
13W	Φ70mm	5730-12V-2W-7D	≥0.5	1123.31LM
18W	Φ80mm	5730-12V-2W-10D	≥0.5	1540.38LM
28W	Φ100mm	5730-12V-2W-14D	≥0.5	2195.79LM
38W	Φ115mm	5730-12V-2W-20D	≥0.5	3058LM
48W	Φ125mm	5730-12V-2W-26D	≥0.5	3638LM
58W	Φ140mm	5730-12V-2W-26D	≥0.5	4093LM

BANG BANG BULB 9V

棒棒灯

CRI
>80

2
YEAR
WARRANTY

3200K/6500K



• **Hight quality Pc cover**
light transmittance is
more than 90%



• **Imported LED Chips**
SMD 2835,
Luminous efficency>120lm/w
luminous maintenace>95% at
30000h.Ra>80



• **Hight quality driver**
wide range of voltage
power wiht high curren
accuracy and perfect
protection



• **Aluminum**
PBT body,Mechanical strength and
fire retardant, good heat dissipation
ability,Hermetically sealed and
complete insulation



• **Standard copper E27/B22
for options**
Good electric conduction and
good mechanical strength



Wattage 瓦数	Diameter Size 灯体尺寸	Led chip 灯珠	PF 功率因素	Total LM 总流明
5W	Φ32mm*H99mm	2835-7D	≥0.5	500LM
10W	Φ36mm*H114mm	2835-10D	≥0.5	783LM
15W	Φ43mm*H133mm	2835-17D	≥0.5	1327LM
20W	Φ52mm*H147mm	2835-23D	≥0.5	1592LM

Four Battery Emergency Bulb

四节电池应急灯球泡



3200K/6500K



USE finger to control the emergency mode



E27/B22 Charging



Lights up when exposed to water



1 battery



2 battery



3 battery



4 battery



Charging Time:3 hrs
Emergency Time:36 Hrs



Wattage 瓦数	Diameter Size 灯体尺寸	Led chip 灯珠	Voltage 电压	PCS/CTN 个/箱	Packing Size 外箱尺寸
40W	φ 90*H170mm	2835-33D	AC85-265V	80	45.5*36.7*66